

	SOCKETS WELDER 32MM OF RJQ-32			SOCKETS WELDER 32MM OF ZRJQ-32	
	Rated voltage:	110V / 220V		Rated voltage:	110V / 220V
	Rated frequency:	50Hz/60Hz		Rated frequency:	50Hz/60Hz
	Rated power:	600W		Rated power:	600W
	Working temp:	260°C		Working temp:	260°C
	Temp.Tolerance:	±5°C		Temp.Tolerance:	±5°C
	Warning temp.:	295°C		Warning temp.:	295°C
	Welding size:	20-25-32mm		Welding size:	20-25-32mm
	Suit material:	PP-R/PE/PB		Suit material:	PP-R/PE/PB
	G.W:	1.6 kgs		Net weight:	1.6 kgs
	Pcs/Ctn:	5 pcs		Pcs/Ctn:	5 pcs
	Net weight:	23.6 kgs		G.W:	23.6 kgs
Dimension(mm):	440*270*540	Dimension(mm):	440*270*540		

	SOCKETS WELDER 32MM OF THJ-32			SOCKETS WELDER 32MM OF ZTHJ-32	
	Rated voltage:	110V / 220V		Rated voltage:	110V / 220V
	Rated frequency:	50Hz/60Hz		Rated frequency:	50Hz/60Hz
	Rated power:	600W		Rated power:	600W
	Working temp:	260°C		Working temp:	260°C
	Temp.Tolerance:	±5°C		Temp.Tolerance:	±5°C
	Warning temp.:	295°C		Warning temp.:	295°C
	Welding size:	20-25-32mm		Welding size:	20-25-32mm
	Suit material:	PP-R/PE/PB		Suit material:	PP-R/PE/PB
	G.W:	21.6 kgs		Net weight:	1.6 kgs
	Pcs/Ctn:	5 pcs		Pcs/Ctn:	5 pcs
	Net weight:	21.6 kgs		G.W:	21.6 kgs
Dimension(mm):	440*270*540	Dimension(mm):	440*270*540		

	SOCKETS WELDER 63MM OF RJQ-63			SOCKETS WELDER 63MM OF ZRJQ-63	
	Rated voltage:	110V / 220V		Rated voltage:	110V / 220V
	Rated frequency:	50Hz/60Hz		Rated frequency:	50Hz/60Hz
	Rated power:	800W		Rated power:	800W
	Working temp:	260°C		Working temp:	260°C
	Temp.Tolerance:	±5°C		Temp.Tolerance:	±5°C
	Warning temp.:	295°C		Warning temp.:	295°C
	Welding size:	20-25-32-40-50-63mm		Welding size:	20-25-32-40-50-63mm
	Suit material:	PP-R/PE/PB		Suit material:	PP-R/PE/PB
	G.W:	17.2 kgs		Net weight:	1.6 kgs
	Pcs/Ctn:	2 pcs		Pcs/Ctn:	2 pcs
	Net weight:	1.8 kgs		G.W:	17.2 kgs
Dimension(mm):	460*270*270	Dimension(mm):	440*270*270		

	SOCKETS WELDER 63MM OF THJ-63			SOCKETS WELDER 63MM OF ZTHJ-63	
	Rated voltage:	110V / 220V		Rated voltage:	110V / 220V
	Rated frequency:	50Hz/60Hz		Rated frequency:	50Hz/60Hz
	Rated power:	800W		Rated power:	800W
	Working temp:	260°C		Working temp:	260°C
	Temp.Tolerance:	±5°C		Temp.Tolerance:	±5°C
	Warning temp.:	295°C		Warning temp.:	295°C
	Welding size:	20-25-32-40-50-63mm		Welding size:	20-25-32-40-50-63mm
	Suit material:	PP-R/PE/PB		Suit material:	PP-R/PE/PB
	G.W:	15.2 kgs		Net weight:	1.6 kgs
	Pcs/Ctn:	2 pcs		Pcs/Ctn:	2 pcs
	Net weight:	1.8 kgs		G.W:	15.2 kgs
Dimension(mm):	460*270*270	Dimension(mm):	440*270*270		

	SOCKETS WELDER 110MM OF RJQ-110			SOCKETS WELDER 110MM OF ZRJQ-110	
	Rated voltage:	110V / 220V		Rated voltage:	110V / 220V
	Rated frequency:	50Hz/60Hz		Rated frequency:	50Hz/60Hz
	Rated power:	1200W		Rated power:	1200W
	Working temp:	260°C		Working temp:	260°C
	Temp.Tolerance:	±5°C		Temp.Tolerance:	±5°C
	Warning temp.:	295°C		Warning temp.:	295°C
	Welding size:	75-90-110mm		Welding size:	75-90-110mm
	Suit material:	PP-R/PE/PB		Suit material:	PP-R/PE/PB
	G.W:	22.8 kgs		Net weight:	2.0 kgs
	Pcs/Ctn:	2 pcs		Pcs/Ctn:	2 pcs
	Net weight:	2.0 kgs		G.W:	22.8 kgs
Dimension(mm):	460*270*270	Dimension(mm):	460*270*270		

	SOCKETS WELDER 110MM OF THJ-110			SOCKETS WELDER 110MM OF ZTHJ-110	
	Rated voltage:	110V / 220V		Rated voltage:	110V / 220V
	Rated frequency:	50Hz/60Hz		Rated frequency:	50Hz/60Hz
	Rated power:	1200W		Rated power:	1200W
	Working temp:	260°C		Working temp:	260°C
	Temp.Tolerance:	±5°C		Temp.Tolerance:	±5°C
	Warning temp.:	295°C		Warning temp.:	295°C
	Welding size:	75-90-110mm		Welding size:	75-90-110mm
	Suit material:	PP-R/PE/PB		Suit material:	PP-R/PE/PB
	G.W:	20.8 kgs		Net weight:	2.0 kgs
	Pcs/Ctn:	2 pcs		Pcs/Ctn:	2 pcs
	Net weight:	2.0 kgs		G.W:	20.8 kgs
Dimension(mm):	460*270*270	Dimension(mm):	460*270*270		